

Decorative Wall and
Ceiling Panel with
Limitless Choices



Nudo Allure™ Technical Data

Class C – Pages 1-4

Class A – Pages 5-8

RESPONSIVENESS

CONSISTENCY

SOLUTIONS

Nudo Allure™ Technical Data Class C

Nudo Allure™ Class C is an interior decorative composite wall and ceiling panel that combines high-pressure laminate decorative patterns and wood grains with a Nudo composite core. The result – a decorative durable wall and ceiling panel that is easy to install.

There are numerous applications that often need durability and moisture resistance, but often wall and ceiling panels such as wood paneling, veneers or vinyl are used to achieve a more decorative look. Allure allows fashion to meet function, with its high resistance to impact, chemicals, and moisture, yet allows you to choose from hundreds of HPL patterns and wood grains.

Physical Properties: Table 1

Property	Typical Value		Test Method
Surface Burn Test	≤ 75 Class C	N/A	ASTM E84
Smoke Development	≤ 20	N/A	ASTM E84
Flexural Strength	11,500	psi	ASTM D790
Flexural Modulus	1,000,000	psi	ASTM D790
Flexural Load	75	lbf	ASTM D790
Tensile Strength	7,350	psi	ASTM D638
Tensile Modulus	1,000,000	psi	ASTM D638
Barcol Hardness	65	65	ASTM D 2583
Izod Impact	2	Ft-lbs/in.	ASTM D256
Water Absorption	3.7%	24 hrs. @ 23° C	ASTM D570
Coefficient of Linear Thermal Expansion	2.46 X 10 ⁻⁵	50% Humidity Temp -23° C	ASTM D696-03



Physical Properties: Table 2

Part Number Identifier	Nominal Panel Thickness	Nominal Panel Weight	Color	Size
AP-C	.150" (3.8mm)	1.0# psf	Selected Patterns and wood grains from various high pressure laminate (HPL) Manufacturers (ie. Arborite, Formica, Wilsonart, Pionite, etc.)	4'X8' (1.2mX2.4M) 4'X10' (1.2MX3M) Non-Standard sizes available made-to-order

SPECIFICATIONS: The Allure panels are manufactured with state-of-the-art laminating equipment and adhesives.

COMPOSITION:

- Decorative paper made with a melamine finish surface.
- Core is an aluminum composite panel with an HDPE center.
- The backer is an adhesive phenolic receptive paper.

FINISHED PANEL QUALITY:

- The backside shall be smooth. Backside imperfections which do not affect functional properties are not cause for rejection.
- Physical properties shall be set forth in Table 1.
- Product quality standards and tolerance for panel weight and thickness shall be set for in Nudo Product, Inc. Quality Control Procedures/Standards which are available upon request.
- Dimensions shall be specified on purchased order, subject to the following tolerances: Width: $\pm 1/8"$ (3.2mm) Length: $\pm 1/8"$ (3.2 mm) Squareness: not more than $1/8"$ (3.2 mm) out of square.
- Panels shall be installed in accordance with the manufacturer's guidelines as set forth in the installation guide.

CERTIFICATION: Meets the minimum requirements of the major model building codes for Class C interior wall and ceiling finishes. Flame spread of less than 200, smoke development less than 450 per ASTM E-84.

FABRICATING RECOMMENDATIONS: Protect your eyes with goggles; cover your nose and mouth with a filter mask when cutting Allure panels. When cutting Allure, position the panel so that the saw blade enters the decorative side first, to avoid chipping and damage.



Hand Fabricating:

- Drilling – high speed drill bit (60° cutting angle, with 12° - 15° clearance) or hole saw.
- Cutting: 72-tooth circular saw with reinforced carborundum or carbide-tipped blade.

STORAGE: Allure should be stored horizontally indoors on a contiguous flat surface. Protective film should remain on the panel until installation. Panels should never be stored on the floor or an outside wall. Optimum storage conditions are 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity.

PRECONDITIONING: Prior to installing Allure, remove the packaging materials and allow the panels to acclimate to room temperature and humidity for at least 48 hours. Ideally, the room temperature and humidity during acclimation and installation should be the same as the final operation conditions. **DO NOT REMOVE PROTECTIVE FILM FROM PANEL SURFACE UNTIL AFTER INSTALLATION AND BUILDING IS AT OPERATIONAL TEMPERATURE CONDITIONS.**

PRODUCT LIMITATIONS: Allure is designed as an indoor decorative panel. It should never be exposed to extremely high or extremely low moisture conditions. Allure is designed to be installed over a solid wall surface and should never be directly installed over studs, concrete, concrete block, or non-insulated exterior walls. Allure should be installed between 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity. Non-compliance with product limitations may affect future performance and voids warranty.

CLEANING INSTRUCTIONS: Allure is easy to clean. In most cases, use a clean, damp, nonabrasive cotton cloth and a mild liquid detergent or household cleaner. Always rinse with clean water and a clean, non-abrasive cotton cloth. Dry the panels with a soft, clean, non-abrasive cotton cloth.

DO NOT USE: abrasive cleaners with bleach, cleaners with acid, alkali or sodium hypochlorite. They will damage and permanently discolor the surface. Be sure that bottles, rags, or other materials with these cleaners never come in contact with the surface.

Examples of harsh cleaners to avoid, include but are not limited to:

- Bleach
- Drain Cleaners
- Metal Cleaners
- Oven Cleaners
- Rust Removers
- Tub and Tile Cleaners
- Lime Scale Remover

REMOVAL OF STAINS: To remove stains, use full strength Fantastik, All Purpose Cleaner, Formula 409, Pine-Sol, or other mild household cleaners. Blot with clean, damp, non-abrasive cotton cloth, and rinse with cleaner water. When recommended cleaner changes its formulation, the change may be harmful to the surface. Nudo Products, Inc. cannot be held responsible for these changes. Follow all directions and warnings on the cleaner label because many are extremely flammable.

Dyes and pharmaceutical products will permanently stain the panels. These include hair dyes and rinses, silver nitrate, laundry bluing, tannic acid, povidone-iodine, dermatological tar compounds, and peroxide. To reduce these stains, apply a paste of baking soda and water on the area to pull out the stain. Do not rub, as the paste will be slightly abrasive. Wipe up the past with a clean, damp, nonabrasive cotton cloth, and rinse with clean water.

Stains that are stubborn or even permanent and may not disappear include: wood stains, cash register inks, newsprint, marking pen inks, indelible ink, food pricing ink, and label inks.

Stubborn stains that may disappear on their own after a short time or after repeated cleaning include food stains, glass rings, water marks, coffee, and tea stains.

FLAME SPREAD AND SMOKE DEVELOPMENT RATINGS: The numerical flame spread, and smoke development ratings are not intended to reflect hazards presented by Nudo Product, Inc. products or any other material under actual fire conditions. These rating are determined by small-scale tests conducted by Underwriters Laboratories and other independent testing facilities using the American Society for Testing and Materials E-84 test standards (commonly referred to as the "Tunnel-Test"). NUDO PRODUCTS, INC PROVIDES THESE RATING FOR MATERIAL COMPARISION PURPOSES ONLY. Like other organic building materials, (e.g. wood), panels made up of composite material will burn. When ignited, it may produce dense smoke very rapidly. All smoke is toxic. Fire safety requires proper design of facilities and fire suppression systems, as well as precautions during construction and occupancy. Local codes, insurance requirements and any special needs of the product user will determine the correct fire-rated interior finish and fire suppression system necessary for a specific installation.

Disclaimer: We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions of use are beyond our control, the user assumes all risks. Nothing herein shall be construed as a recommendation for use that infringes on valid patent or as extending a license under valid permit.

RESPONSIVENESS

CONSISTENCY

SOLUTIONS

Nudo Allure™ Technical Data Class A

Nudo Allure™ Class A is an interior decorative composite wall panel that combines high-pressure laminate decorative patterns and wood grains with a Nudo composite core. The result – a decorative durable wall panel that is easy to install.

There are numerous applications that often need durability and moisture resistance, but often wall coverings such as wood paneling, veneers or vinyl are used to achieve a more decorative look. Allure allows fashion to meet function, with its high resistance to impact, chemicals, and moisture, yet allows you to choose from hundreds of HPL patterns and wood grains.

Physical Properties: Table 1

Property	Typical Value		Test Method
Surface Burn Test	≤ 15 Class A	N/A	ASTM E84
Smoke Development	≤ 45	N/A	ASTM E84
Flexural Strength	11,643	psi	ASTM D790
Flexural Modulus	1,014,485	psi	ASTM D790
Flexural Load	78	lbf	ASTM D790
Tensile Strength	7,361	psi	ASTM D638
Tensile Modulus	1,091,364	psi	ASTM D638
Elongation	1.8	%	ASTM D638
Barcol Hardness	67	65	ASTM D 2583
Izod Impact	1.7115	Ft-lbs/in.	ASTM D256
Water Absorption	3.7%	24 hrs. @ 23° C	ASTM D570
Coefficient of Linear Thermal Expansion	2.46 X 10 ⁻⁵	50% Humidity Temp -23° C	ASTM D696-03



Physical Properties: Table 2

Part Number Identifier	Nominal Panel Thickness	Nominal Panel Weight	Color	Size
AP-FR	.150" (3.8mm)	1.0# psf	Selected Patterns and wood grains from various high pressure laminate (HPL) Manufacturers (ie. Arborite, Formica, Wilsonart, Pionite, etc.)	4'X8' (1.2MX2.4M) 4'X10' (1.2MX3M) Non-Standard sizes available made-to-order

SPECIFICATIONS: The Allure panels are manufactured with state-of-the-art laminating equipment and adhesives.

COMPOSITION:

- Decorative paper made with a melamine finish surface.
- Core is an aluminum composite panel with an HDPE center.
- The backer is an adhesive phenolic receptive paper.

FINISHED PANEL QUALITY:

- The backside shall be smooth. Backside imperfections which do not affect functional properties are not cause for rejection.
- Physical properties shall be set forth in Table 1.
- Product quality standards and tolerance for panel weight and thickness shall be set for in Nudo Product, Inc. Quality Control Procedures/Standards which are available upon request.
- Dimensions shall be specified on purchased order, subject to the following tolerances: Width: $\pm 1/8"$ (3.2mm) Length: $\pm 1/8"$ (3.2 mm) Squareness: not more than $1/8"$ (3.2 mm) out of square.
- Panels shall be installed in accordance with the manufacturer's guidelines as set forth in the installation guide.

CERTIFICATION: Meets the minimum requirements of the major model building codes for Class A interior wall finishes. Flame spread of less than 25, smoke development less than 450 per ASTM E-84.

FABRICATING RECOMMENDATIONS: Protect your eyes with goggles; cover your nose and mouth with a filter mask when cutting Allure panels. When cutting Allure, position the panel so that the saw blade enters the decorative side first, to avoid chipping and damage.



Hand Fabricating:

- Drilling – high speed drill bit (60° cutting angle, with 12° - 15° clearance) or hole saw.
- Cutting: 72-tooth circular saw with reinforced carborundum or carbide-tipped blade.

STORAGE: Allure should be stored horizontally indoors on a pallet with a contiguous flat surface. Protective film should remain on the panel until installation. Panels should never be stored on the floor or an outside wall. Optimum storage conditions are 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity.

PRECONDITIONING: Prior to installing Allure, remove the packaging materials and allow the panels to acclimate to room temperature and humidity for at least 48 hours. Ideally, the room temperature and humidity during acclimation and installation should be the same as the final operation conditions. **DO NOT REMOVE PROTECTIVE FILM FROM PANEL SURFACE UNTIL AFTER INSTALLATION AND BUILDING IS AT OPERATIONAL TEMPERATURE CONDITIONS.**

PRODUCT LIMITATIONS: Allure is designed as an indoor decorative panel. It should never be exposed to extremely high or extremely low moisture conditions. Allure is designed to be installed over a solid wall surface and should never be directly installed over studs or non-insulated exterior walls. Allure should be installed between 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity. Noncompliance with product limitations may affect future performance and voids warranty.

CLEANING INSTRUCTIONS: Allure is easy to clean. In most cases, use a clean, damp, nonabrasive cotton cloth and a mild liquid detergent or household cleaner. Always rinse with clean water and a clean, non-abrasive cotton cloth. Dry the panels with a soft, clean, non-abrasive cotton cloth.

DO NOT USE: abrasive cleaners with bleach, cleaners with acid, alkali, or sodium hypochlorite. They will damage and permanently discolor the surface. Be sure that bottles, rags, or other materials with these cleaners never come in contact with the surface.

Examples of harsh cleaners to avoid, include but are not limited to:

- Bleach
- Drain Cleaners
- Metal Cleaners
- Oven Cleaners
- Rust Removers
- Tub and Tile Cleaners
- Lime Scale Remover

REMOVAL OF STAINS: To remove stains, use full strength Fantastik, All Purpose Cleaner, Formula 409, Pine-Sol, or other mild household cleaners. Blot with clean, damp, non-abrasive cotton cloth, and rinse with cleaner water. When recommended cleaner changes its formulation, the change may be harmful to the surface. Nudo Products, Inc. cannot be held responsible for these changes. Follow all directions and warnings on the cleaner label because many are extremely flammable.

Dyes and pharmaceutical products will permanently stain the panels. These include hair dyes and rinses, silver nitrate, laundry bluing, tannic acid, povidone-iodine, dermatological tar compounds, and peroxide. To reduce these stains, apply a paste of baking soda and water on the area to pull out the stain. Do not rub, as the paste will be slightly abrasive. Wipe up the past with a clean, damp, nonabrasive cotton cloth, and rinse with clean water.

Stains that are stubborn or even permanent and may not disappear include: wood stains, cash register inks, newsprint, marking pen inks, indelible ink, food pricing ink, and label inks.

Stubborn stains that may disappear on their own after a short time or after repeated cleaning include food stains, glass rings, water marks, coffee, and tea stains.

FLAME SPREAD AND SMOKE DEVELOPMENT RATINGS: The numerical flame spread, and smoke development ratings are not intended to reflect hazards presented by Nudo Product, Inc. products or any other material under actual fire conditions. These rating are determined by small-scale tests conducted by Underwriters Laboratories and other independent testing facilities using the American Society for Testing and Materials E-84 test standards (commonly referred to as the "Tunnel-Test"). NUDO PRODUCTS, INC PROVIDES THESE RATING FOR MATERIAL COMPARISION PURPOSES ONLY. Like other organic building materials, (e.g. wood), panels made up of composite material will burn. When ignited, it may produce dense smoke very rapidly. All smoke is toxic. Fire safety requires proper design of facilities and fire suppression systems, as well as precautions during construction and occupancy. Local codes, insurance requirements and any special needs of the product user will determine the correct fire-rated interior finish and fire suppression system necessary for a specific installation.

Disclaimer: We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions of use are beyond our control, the user assumes all risks. Nothing herein shall be construed as a recommendation for use that infringes on valid patent or as extending a license under valid permit.

RESPONSIVENESS

CONSISTENCY

SOLUTIONS