

# TECHNICAL DATA SHEET

## Materials Specifications for materials used in Nudo Wall Protection Products

### Copolymer (PETG) Extrusions

Material: Provista Copolymer (or equivalent)

PROPERTIES	TEST METHOD	VALUE
Specific Gravity	ASTM D-792	1.31
Tensile Yield Strength, psi	ASTM D-638	7690
Tensile Elongation Yield	ASTM D-638	5.0%
Tensile Modulus, psi	ASTM D-638	320000
Flexural Yield Strength, psi	ASTM D-790	10400
Flexural Modulus, psi	ASTM D-790	305000
Notched Izod Impact Strength ft-lbs/in	ASTM D-256	.78 (-40°F) 1.4 (73°F)
Hardness, Shore R	ASTM D-785	110
Deflection Temperature Under Load		
66 psi, Unannealed	ASTM D-648	154°F
264 psi, Unannealed	ASTM D-648	144°F

---

Provista Copolymer NXT has been GREENGUARD INDOOR AIR QUALITY CERTIFIED®

---

1500 Taylor Avenue  
Springfield, IL 62703

(800) 826-4132 *main*  
(217) 528-8722 *fax*

info@nudo.com  
www.nudo.com

**NUDO**®  
YOUR VISION IS OUR MISSION™