

Moisture Resistant  
Transportation Liner  
Panel



Nudo Utilite™ Transportation Liner Technical Data

NUDO Utilite™ Transportation Liner Panels are an interior Class A interlocking liner panel. These seamless fluted vinyl liner panels are 16" and 24" wide, and come in 8', 12', 16' and 20' lengths. The Utilite™ liner panel is a high gloss bright white finish, durable, lightweight, and are easy to easy to maintain.

Physical Properties: Table 1

Property	Typical Value*		Test Method
	Class A	N/A	
Surface Burn Test	Class A	N/A	ASTM E84
Flame Spread	20	N/A	ASTM E84
Smoke Development	≤ 250	N/A	ASTM E84
Surface Burn Test - Canadian	Class A	N/A	ULCS 102.2
Flexural Strength	2,223	psi	ASTM D790
Flexural Modulus	156,976	psi	ASTM D790
Flexural Load	10,496	lbf	ASTM D790
Tensile Strength	1,308	psi	ASTM D638
Izod Impact	1.57	Ft-lbs/in.	ASTM D256

\*These are typical values and are not to be construed as specific product limits

Physical Properties: Table 2

Part Number Identifier	Nominal Panel Thickness	Nominal Panel Weight	Color	Size
NP-400*	.400" (10mm)	1.0# psf	White High Gloss	16"X8', 10', 12' 16', 20' 24"X8', 10', 12', 16', 20'



### Utilite™ Transportation Liner Panel

**Composition:** The Utilite Transportation Liner panel is a seamless tongue and groove plastic panel composed of fluted PVC.

**Preconditioning:** Prior to installing Utilite panels, remove the packaging materials and allow the panels to acclimate to room temperature and humidity for at least 48 hours.

**Product Limitations:** NUDO Utilite™ Transportation Liner Panels factory is designed as an interior panel. When installing keep panels 24" from Heater and shield Radiant Tube Heater. Utilite is designed to be installed over a solid wall surface or directly installed over non insulated exterior walls. Utilite should be installed between 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity. Do not install panels using Power Nail Guns or Staples, use only recommended fasteners per manufacturers installation guidelines. If any portion of the panels is not deemed acceptable, notify Nudo immediately. Upon verification of unacceptable panels, Nudo will replace that portion of the material, but will not take responsibility for the labor, other handling, or installation expenses.

#### **Finished Panel Quality, Fabrication & Handling**

- The backside shall be smooth. Backside imperfections which do not affect functional properties are not cause for rejection.
- Physical properties shall be set forth in Table 1.
- Product quality standards and tolerance for panel weight and thickness shall be set for in Nudo Product, Inc. Quality Control Procedures/Standards which are available upon request.
- Panels shall be installed in accordance with the manufacturer's guidelines as set forth in the installation guide lines.
- Please refer to NUDO Utilite™ Installation Guidelines for cleaning instructions.
- Panels can be installed and fabricated with the same tools and techniques as ordinary plastic panels. Carbide-tipped tools are recommended, as well as safety equipment. Eye protection and filtered mask should be worn during cutting and trimming operations.

**Storage:** Utilite panels should be stored horizontally indoors on a contiguous flat surface. Panels should never be stored on the floor or an outside wall. Storage conditions are 60°F (16°C) to 75°F (24°C) and 35% to 55% relative humidity.

**Disclaimer:** We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions of use are beyond our control, the user assumes all risks. Nothing herein shall be construed as a recommendation for use that infringes on valid patent or as extending a license under valid permit. Nothing herein shall be construed as a recommendation for use or as extending a license under valid patent.

RESPONSIVENESS

CONSISTENCY

SOLUTIONS